



# ACCURATE

COLOR-THRU  
Phenolic!

**PRICED THE  
SAME  
AS REGULAR  
PHENOLIC!**

The Phenolic toilet partition with constant "**Color-Thru!**" Color-Thru adds to the partition of choice when strength, durability and low maintenance are desired.

- Effective for impact resistance, scratch resistance and graffiti resistance plus excellent screw holding power.
- Convenient Shipment in 10 days with no added cost.
- Available in all styles for full flexibility in design and application.

Available in FIVE attractive colors



Sea Spray



Red Clay



Camel



Moss



Black

**IT'S ALL ACCURATE.**

See other side for Specifications.

**Accurate**

Accurate Partitions Corp.

# Specifications

## Color-Thru Phenolic Partitions

*with Floor Anchored Overhead Braced Mounting Style*

---

### Part 1: General

#### 1.01 Work Included

A - The toilet partitions shall be "COLOR-THRU" phenolic material with floor anchored/overhead braced mounting style as manufactured by Accurate Partitions Corp., Lyons, Illinois.

B - Furnish all labor and materials necessary for completion of work in this section, as shown in the approved drawings and specified herein.

1.02 Related Work - Specified elsewhere, shall include accessories and anchorage/blocking for attachment of partitions.

---

### Part 2: Product

2.01 **Doors and Pilasters** - Shall be solid phenolic core with decorative surface sheet on both faces and an overall thickness of ¾". Phenolic core color shall be the same as the decorative surface sheets.

2.02 **Panels and Urinal Screens** - Shall be solid phenolic core with decorative surface sheet on both faces and an overall thickness of ½". Phenolic core color shall be the same as the decorative surface sheets.

2.03 **Material** - Doors, panels, pilasters and urinal screens shall be fabricated from phenolic material comprised of multiple layers of resin-impregnated kraft paper with a decorative surface sheet on both faces. Kraft paper, phenolic resin and decorative face sheets shall all be the same color and shall be fused together under high temperature and pressure.

2.04 **Finish** - All components shall be water-resistant. All edges shall be the same color as the face sheets and machine-finished with chamfered edges.

2.05 **Color** - Shall be selected from Accurate's full range of designer COLOR-THRU phenolic colors.

2.06 **Door Hardware** - Shall be gravity cam-action hinge that permits door to return to a pre-set position when not locked. Hinge, strike and keeper shall be cast stainless steel or Zamac with brushed finish to resist corrosion, and shall be through-bolted to doors and pilasters with vandal-resistant stainless steel shoulder screws and barrel nuts. Cam-action hinge shall allow emergency access by lifting the door from the bottom.

2.07 **Mounting Hardware** - Cast stainless steel or Zamac stirrup brackets with brushed finish shall be secured to walls and pilasters with vandal-resistant stainless steel fasteners. Panels shall be through-bolted with vandal-resistant stainless steel shoulder screws and barrel nuts.

2.08 **Construction Design** - Partitions shall be anchored to floor by ¼" x 1" stainless steel mounting bar attached to the bottom of each pilaster. Each mounting bar shall be secured to floor with 3/8" zinc plated bolts. Floor anchoring system shall be concealed by a type 304 stainless steel trim shoe with a #4 finish. Aluminum headrail with anti-grip profile shall provide overhead bracing and span all partitions and brace the end pilaster to the back wall.

---

### Part 3: Execution

3.01 **Installation** - Material shall be installed in accordance to manufacturer's installation instructions with partitions rigid, straight and plumb. Doors and panels shall be mounted 12" above the finished floor.

3.02 **Warranty** - Accurate Partitions Corp. guarantees its COLOR-THRU phenolic partitions, when properly maintained, against delamination, breakage, or corrosion for 10 YEARS from the date of receipt by the customer. If material is found to be defective during that period, the material shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.