

## **SPECIFICATION**

Surface Mounted Soap Reservoir Unit shall have a capacity of 1 to 2-1/2 gallons (see chart). Reservoir tank and top cover shall be fabricated of alloy 18-8 stainless steel, type 304, 22 gauge. All exposed surfaces shall be  $N^{\circ}$  4 satin finish and be protected during shipment with a PVC film easily removable after installation. Bottom of tank shall be fitted with a 3/8" NPT female coupling. Tank shall have no exposed fastening devices or spot welded seams. A leak proof positive acting liquid level indicator shall be provided. A separate concealed stainless steel wall plate with mounting holes shall be provided.

Surface Liquid Soap Reservoir shall be Model :	№0377	Nº 0378	]
as manufactured by American Specialties, Inc. 441	Saw Mill Ri	iver Road Yonk	ers, New York 10701-4913

## INSTALLATION

Wall plate is anchored to wall or partition through three (3) concealed mounting holes. Reservoir is then installed over wall plate. Recommended mounting location is 6" minimum above soap valves. Recommended soap valves are Models N° 0375 or N° 0353.

## **OPERATION**

Soap is dispensed by opening shut-off valve on unit. A level gauge on unit indicates amount of soap in tank. Unit may be reloaded at anytime with a partial load in-place. Tank supply is replenished manually on cycle determined by maintenance needs.

## **OPTIONS**

						Distributed by
ſ	Model Nº	Capacity in Gallons (L)	Width (mm)	Height (mm)	Depth (mm)	www.AmeraProducts.com
	0377	1 (3.8)	9-7/8" (251)	8-1/4" (210)	4-3/8" (111)	Phone: (800) 608-6568 Fax: (409) 840-5545
[	0378	2-1/2 (9.5)	12-3/8" (314)	10" (254)	5-3/4" (146)	info@ameraproducts.com
		•				
	Accessor	y Specialties	AMERIC	AN DISPENSER	Desert Ray	Products WATROUS INC.

THIS MANUFACTURER RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN OR DIMENSIONS WITHOUT FORMAL NOTICE