

SESAME ACCESS DOOR

MODEL KSTDW

For Drywall Ceilings



DATE

PROJECT DATA

SPECIFICATIONS

GENERAL SCOPE:

Access doors shall be Karp Type KSTDW as manufactured by Karp Associates, Inc., Maspeth, N.Y.

Sizes shall be as indicated on the drawings.

CONSTRUCTION:

- 1. Frame shall be 20 gage galvanized steel.
- 2. Door shall be 20 gage galvanized steel and shall be lined with 3/8" mineral fiberboard.
- 3. Gasketing shall be flame retardant polyurethane.
- 4. Locks shall have plastic grommets and shall be square head key wrench operated.
- 5. Hinge shall be concealed pivot with a controlled action device (CAD), except for size 12" x 12".

STANDARD SIZES

Phone: (800) 608-6568 Fax: (409) 840-5545 nfo@ameraproducts.com

DOOR SIZE H x W (INCHES)	SHIPPING WT. (LBS.)		
12 x 12	8.2		
18 x 18	16.7		
24 x 24	17.6		
36 x 24	44.4		
48 x 24	32.6		

		PRU	DECID	AIA		
Project	Name:					
Archite	ct:					
Contrac	ctor:					
Agent/0	Customer	Name:				
Tagging	j Instructi	ons:				
Special	Instructio	ns'				
PROJECT SCHEDULE						
Qty.	Н	w	No. of Latches	Finish	Remarks	
					F 1"	
	Г	ı i				

w

Made with Union Labor

