

# Insulated Fire-Rated

## ACCESS DOOR

Designed for wall and ceiling applications, this fire-rated Insulated Access Door is UL and Warnock-Hersey listed. Engineered with mineral fiber to assist in reducing heat transfer in the event of a fire.

### FEATURES

**FIRE-RATED** Independently tested and labeled for 1-1/2 hours for wall applications and 3 hours for ceiling applications.

**EASY OPERATION** This self-closing door features an inside knurled knob latch release that is easy to operate.

**CUSTOM SIZING** Custom sizes available from 6 inches by 6 inches to 48 inches by 48 inches.



### DETAILS

**DOOR** 20 gauge Steel, Self-Closing

**FRAME** 16 gauge Steel

#### SIZE

- Min: 6 inches by 6 inches
- BIT Max: 24 inches by 72 inches or 48 inches by 48 inches
- BIW/BIP Max: 36 inches by 48 inches

**INSTALLATION** Ceiling or Wall

#### HINGE

- BIT: Flush Continuous Piano
- BIW/BIP: Concealed Pin

**FINISH** White Powder Coat

**INSULATION** 2 inch Thick, Fire-Rated Mineral Fiber, R-8

#### CERTIFICATION

- UL listed "B" label for 1-1/2 hours (Wall)
- Warnock-Hersey listed for 3 hours (Ceiling)

### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BI</b>				<b>X</b>		
	<b>T</b> 1 inch Flange <b>W</b> Drywall Bead <b>P</b> Plaster Bead	<b>K</b> Knurled Knob / Key Operated Latch Bolt <b>M</b> Mortise Lock (1-1/8") Prep	<b>Standard Sizes (W x L)</b> 8" x 8"    18" x 24"    24" x 48" 10" x 10"    20" x 30"    30" x 30" 12" x 12"    22" x 22"    32" x 32" 12" x 18"    22" x 30"    36" x 36" 12" x 24"    22" x 36"    36" x 48" 14" x 14"    24" x 24"    48" x 48" 16" x 16"    24" x 30" 18" x 18"    24" x 36"			<b>B</b> Galvannealed <b>G</b> Gasketing <b>M</b> Masonry Anchors <b>S</b> Type 304 Stainless Steel

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.  
\*Wall application only.

### MATERIALS



White Powder Coat


### FLANGES



1 inch Flange



Drywall Bead




Plaster Bead

### LATCHES



Knurled Knob



Mortise Lock Prep

