

Top Security

ACCESS DOOR

Babcock-Davis' Top Security Access Door is manufactured with detention-grade materials and provides access through openings in walls. The pan style access door includes a heavy-duty butt hinge welded on the surface of the door to prevent unwanted access.



DETAILS

- DOOR** 7 gauge Steel
- FRAME** 3/16 inch Steel Angle - 2 inches by 3 inches
- SIZE**
 - Min: 8 inches by 8 inches
 - Max: 48 inches by 54 inches
- INSTALLATION** Wall
- FLANGE** Exposed
- HINGE** Surface Mounted Heavy-Duty Butt
- PAN DEPTH** 1-1/4 inch
- FINISH** White Powder Coat

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
BTS			X		
	D Detention Lock Prep	Standard Sizes (W x L) 12" x 12" 22" x 30" 24" x 40** 16" x 16" 24" x 24" 24" x 48** 18" x 18" 24" x 36**			G Gasketing M Masonry Anchors S Type 304 Stainless Steel
	M Mortise Lock (1-1/8") Prep				
	S Security Screws				

*Rough opening is door size + 3/4 inch minimum.
 Additional sizes available, call for more information.
 Recommended for Wall surfaces only.

Draft Stop

ACCESS DOOR

Babcock-Davis' Draft Stop Door is a non-rated access door designed to provide access through wall openings in the attics where draft stop conditions are needed. This self-closing and self-latching access door allows for access from both sides of the door.



DETAILS

- DOOR** 14 gauge Steel (self-closing)
- FRAME** 16 gauge Steel
- SIZE**
 - Min: 6 inches by 6 inches
 - BDT Max: 24 inches by 72 inches, 36 inches by 60 inches or 48 inches by 48 inches
 - BDW Max: 36 inches by 48 inches
- INSTALLATION** Wall
- FLANGE** Exposed or Drywall Bead
- HINGE**
 - BDT: Flush Continuous Piano
 - BDW/BDP: Concealed Pin
- FINISH** White Powder Coat

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
BD				X		
	T 1 inch Flange	D Detention Prep	Standard Sizes (W x L) 12" x 12" 22" x 30" 24" x 40** 16" x 16" 24" x 24" 24" x 48** 18" x 18" 24" x 36**			B Galvanized G Gasketing S Type 304 Stainless Steel
	W Drywall Bead	K Knurled Knob/Key Operated Latch Bolt				
	P Plaster Bead	M Mortise Lock (1-1/8") Prep				

*Rough opening is door size +1/4 inch minimum. Additional sizes available, call for more information.
 Recommended for Wall surfaces only.