


CLEANING INSTRUCTIONS - METAL CABINETS

- Our cabinets by are designed to be maintenance free. However, it is recommended that the outer surface of the cabinet, and the hinge area, be kept clear from debris and dirt, to ensure correct operation of the hinged door.
- If latches, locks or hinges need to be lubricated, use a “3 in 1” type light oil, removing excess with a cloth.

| Finish | Description | Cleaning & Maintenance |
|---------------|--|--|
| Painted Steel | Baked-on Powder Coat Paint | Use a soft cloth and mild soap and water. |
| Aluminum | Aluminum Without Clear Coat | |
| 313/315/Clear | Anodized Aluminum - Dark Bronze, Black , Clear | |
| US3 | Polished Clear Coated Brass | Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all lacquer and totally refinish the product. |
| US4 | Satin Clear Coated Brass | |
| US9 | Polished Clear Coated Bronze | |
| US10 | Satin Clear Coated Bronze | |
| US10B | Oxidized & Oiled Bronze | Use a soft cloth and a paste furniture wax. Buff lightly so as not to remove the dark oxide coating where it remains. |
| US32 | Polished Stainless Steel | Use a soft cloth and mild soap and water solution. After cleaning, thoroughly rinse with clear water to remove all traces of the solution and wipe dry to prevent water marks from forming. Stains which resist that treatment can usually be removed by polishing in the direction of the grain with a soft cloth and a non-abrasive stainless steel polish. Test in an unobtrusive area. |
| US32D | Satin Stainless Steel | |

| | |
|--|---|
|  <small>JL INDUSTRIES</small> | <h3>CLEANING INSTRUCTIONS - METAL CABINETS</h3> |
| <p>HEADQUARTERS & CUSTOMER SERVICE: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416 ACPG SOUTHEAST (THOMAS ENTERPRISES): FT MEYERS, FL * ACPG WEST COAST (SAMSON MFG): COMMERCE, CA ACPG WAREHOUSES: DALLAS TX, LANCASTER PA, ATLANTA GA, CHICAGO, IL, SEATTLE WA 1-5-2011</p> | |



Distributed by
www.Ameraproducts.com
 Phone: (800) 608-6568
 Fax: (409) 840-5545
info@ameraproducts.com