Crownline Cabinets Provide A Wide Selection of Door Styles, Glazing and Sizes. These Durable Cabinets are Designed to Industry Standards for Fire Department Valves, Fire Hose Rack Units and Extinguishers.

Door & Trim: #4 Brushed finish stainless steel. 1-3/4" Trim on face and door. These flush cabinet doors are mounted in a 5/8" door stop, are attached by a continuous hinge, and are equipped with zinc-plated handle and roller catch for all non-locking doors. Theft-deterrent SAF-T-LOK™ also available.

Trim Style and Depth: 1-3/4" face trim on frame and 1-1/4" trim on door. Recessed - 3/8" flat trim. Semi-recessed - 1-1/4" Square Edge or 2-1/2" Rolled Edge. Surface mounted - Rolled edge. See separate submittal for trimless models.

Tub: CRS, white powder-coat finish standard. Surface-mounted tubs are of the same material as the door and trim.

Knockouts: K.O's are provided on both sides of the cabinet. K.O.'s on left side will be located using "J" dimension, K.O.'s on right side using "K" dimension and may be offset from K.O.'s on "J" side of cabinet. Models 6037 & 6237 - Specify knockout location. Provided on surface mounted cabinets by request. Custom location K.O.'s available. See Page 2 for Drawing of K.O. locations. Not provided with stainless tub option.

Special Features: Models 8035, 8036, 8037 & 8039 have a shelf 12" from the bottom of the cabinet and are designed to hold a fire extinguisher plus F.D. valve or other accessory. Those models can be ordered without shelf to allow for lower mounting height of valve piping to meet NFPA14.


Fire-Rated Option Available: Yes - See separate submittal.

ADA Cabinet Mounting Height: Standard Pull on G, E, W, A,L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door.

STEP 1: SELECT MODEL NUMBER, TRIM & QUANTITY (Refer to Chart on Page 2)

STEP 2: SELECT DOOR STYLE (Check one box below) Full Glazing L22 Solid with SAF-T-LOK G Full Glazing with SAF-T-LOK Vertical Duo W Vertical Duo with SAF-T-LOK Horizontal Duo Panel Horizontal Duo Panel with SAF-T-LOK B10 Acrylic View Window with SAF-T-LOK A Center Duo Panel with SAF-T-LOK L24 Solid with Cylinder Lock & No Handle S21 Solid Door **STEP 3: SELECT DOOR GLAZING** (Check one box below) 10 Clear Acrylic **16** Gray Acrylic 13 Clear Wire Glass with Safety Film 17 Clear Tempered Glass 15 Bronze Acrylic 18 Laminated Safety Glass STEP 4: OPTIONAL FEATURES AT ADDITIONAL COST:






V - Vertical duo panel

F - Full glass with pull G - Full glass with pull handle and Saf-T-Lok (Not Shown)

D - Horizontal duo panel with pull F - Horizontal duo panel with pull and Saf -T-Lok. (Not Shown)

with pull W - Vertical due panel with pull and Saf-T-Lok. (Not Shown)




S21 - Solid with pull L22 - Solid with pull and Saf-T-Lok L24 - Solid with cylinder key lock/no pull (L22,24 not shown)

B10 - Acrylic view window with pull, and Saf-T-Lok

A - Horizontal duo panel with pull and Saf-T-Lok


Fax: (409) 840-5543 info@ameraproducts.com


#6 Matte Finish Stainless Steel Door & Trim	PRH Recessed Pull Handle	Black Vertical FE Letters LDCVBFE
#7 Polished Stainless Steel Door & Trim	PUCH Polished Chrome Pull	Red Vertical FE Letters LDCVRFE
#8 Mirror Finish Stainless Steel Door & Trim	FDVO Decal Fire Department Valve Octagonal 6 x 6"	White Vertical FE Letters LDCVWFE
# 4 Finish Stainless Tub	1403 Decal Fire Hose Black/Red Horiz. Letters 4 x 9	Black Horizontal FE Letters LDCHBFE
Optional Tub Color: BlackRed	LDCHRFDV-R Diecut Fire Dept. Valve Horiz.10-1/4 x 4-3/8	Red Horizontal FE Letters LDCHRFE
SA Strobe Alarm (surface mount models)	LDCVRFDV Diecut Fire Dept Valve Vert. 3/4" x 211/2"	White Horizontal FE Letters LDCHWFE
CA Commander Alarm	LDCVRFDV-R Diecut Fire Dept Valve Vert. Rever. 3/4" x 211/2"	Etched or Engraved Lettering -
BA Brigadier Alarm	LDCHRFDV Diecut Fire Department Valve Ascend. 1" x 17"	Check box and attach separate submitta
Futura "Fire" Handle Mill Red White	LDCVRFSCV-R Diecut Fire Sprinkler Cont. Valve Vert 3/4" x 18"	Fire Hose Racks - See separate submitt
No Shelf for 8000 Series	-	



SUBMITTAL: CROWNLINE VALVE & HOSE CABINETS - STAINLESS STEEL

Distributed by
www.AmeraProducts.com
Phone: (800) 608-6568
rax: (409) 840-3545
info@ameraproducts.com





-	ا ا													ARE TRIM OPTIONAL ROLLED EDGE	
TRIM	& D	OOR MATERIAL & SERIES). W x H x Inches	D in	FRAME	O.D.		RECESSED WALL OPENING		KNOCKOUT LOCATIONS			RECOMMENDED HOSE RACK, FIRE DEPARTMENT VALVES &	
QTY #		TRIM STYLE	Α	В	C	Е	F	Width	Height	Depth	J	G	K	EXTINGUISHERS	
				Cabinet	ts with	Hose Ra	ack and	Extingu	isher or	Fire De	partmen	ıt Va	lve		
60		FLAT TRIM 3/8"	24	30	6	27 3/8	33 3/8	25	31	5 7/8	2 1/2	4	2 1/2	HOSE RACK:	
60	36	1-1/4" SQUARE EDGE	24	30	6	27 3/8	33 3/8	25	31	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit - 50 or 75' Hose (HRA050B, HRA050CH,	
60	37	2-1/2" ROLLED EDGE	24	30	6	27 3/8	33 3/8	25	31	3 5/8	Specify \	When	Ordering	HRA075B, HRA075CH) & Cosmic 2.5 or	
60	39	SURFACE MOUNTED	27 3/16	33 3/16	6 1/2	27 3/8	33 3/8	-	_	-	Upon	Req	uest	Galaxy 2.5-5 lb Extinguisher	
62	35	FLAT TRIM 3/8"	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	5 7/8	2 1/2	4	2 1/2	HOSE RACK:	
62	36	1-1/4" SQUARE EDGE	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit -100' Hose	
62	37	2-1/2" ROLLED EDGE	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	3 5/8	Specify \	When	Ordering		
62	39	SURFACE MOUNTED	27 3/16	37 15/16	6 1/2	27 3/8	38 1/8	-	-	-	Upo	n Re	quest		
61	35	FLAT TRIM 3/8"	24	30	8	27 3/8	33 3/8	25	31	7 7/8	4	4	2 1/2	HOSE RACK: 2-1/2" x 1-1/2" Hose Rack Unit -	
61	36	1-1/4" SQUARE EDGE	24	30	8	27 3/8	33 3/8	25	31	6 7/8	4	4	2 1/2		
61	37	2-1/2" ROLLED EDGE	24	30	8	27 3/8	33 3/8	25	31	5 5/8	4	4	2 1/2	50 or 75' Hose	
61	39	SURFACE MOUNTED	27 3/16	33 3/16	8 1/2	27 3/8	33 3/8	_	-	-	Upo	n Re	quest	(H4A050B-2.5 OR HRA075B-2.5)	
64	35	FLAT TRIM 3/8"	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	7 7/8	4	4	2 1/2		
64	36	1-1/4" SQUARE EDGE	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 7/8	4	4	2 1/2	HOSE RACK:	
64	37	2-1/2" ROLLED EDGE	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	5 5/8	4	4	2 1/2	2-1/2" x 1-1/2" Hose Rack Unit - 100' Hose (HRA100B-2.5)	
64	39	SURFACE MOUNTED	27 3/16	37 15/16	8 1/2	27 3/8	38 1/8	_	_	_	Upo	n Re	quest	100 1105e (11NA 100D-2.5)	
66	35	FLAT TRIM 3/8"	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	7 7/8	4	4	2 1/2		
66		1-1/4" SQUARE EDGE	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 7/8	4	4	2 1/2	HOSE RACK:	
66	37	2-1/2" ROLLED EDGE	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	5 5/8	4	4	2 1/2	2-1/2" x 1-1/2" Hose Rack Unit - 125' Hose (HRA125B-2.5)	
66		SURFACE MOUNTED	27 3/16	41 15/16	8 1/2	27 3/8	42 1/8	_	_	_	Upo	n Re	quest	125 HUSE (HRA 1256-2.5)	
63		FLAT TRIM 3/8"	30	30	8	33 3/8	33 3/8	31	31	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
		1-1/4" SQUARE EDGE	30	30	8	33 3/8	33 3/8	31	31	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
		2-1/2" ROLLED EDGE	30	30	8	33 3/8	33 3/8	31	31	5 5/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve; 50' or 75' Hose	
—		SURFACE MOUNTED	33 3/16	33 3/16	8 1/2	33 3/8	33 3/8	_	-	_	Uno	n Re	quest	Rack Unit Plus FD Valve or Cosmic or Galaxy Extinguisher	
-		FLAT TRIM 3/8"	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
\vdash		1-1/4" SQUARE EDGE	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
		2-1/2" ROLLED EDGE	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	5 5/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve; 100' Hose Rack	
						36 1/8	38 1/8	33 3/4		3 3/0				Unit Plus FD Valve or Cosmic or Galaxy	
		SURFACE MOUNTED	35 15/16	37 15/16	8 1/2			-	-				quest	Extinguisher	
		FLAT TRIM 3/8"	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE OR EXTINGUISHER:	
\vdash		1-1/4" SQUARE EDGE	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	6 7/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve; 125' Hose Rack	
\vdash		2-1/2" ROLLED EDGE	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	5 5/8	4	4	2 1/2	Unit Plus FD Valve or Cosmic or Galaxy Extinguisher	
72	39	SURFACE MOUNTED	35 15/16	41 15/16	8 1/2	36 1/8	42 1/8	-	-	-	Upo	n Re	quest		
								ire Depa	artment \	Valves					
		FLAT TRIM 3/8"	18	18	8	21 3/8	21 3/8	19	19	7 7/8	4	9	2 1/2		
85	36	1-1/4" SQUARE EDGE	18	18	8	21 3/8	21 3/8	19	19	6 7/8	4	9	2 1/2		
		2-1/2" ROLLED EDGE	18	18	8	21 3/8	21 3/8	19	19	5 5/8	4	9	2 1/2	FIRE DEPARTMENT VALVE:	
		SURFACE MOUNTED	21 3/16	21 3/16	8 1/2	21 3/8	21 3/8	-	-	-			quest	1-1/2" or 2-1/2"	
		FLAT TRIM 3/8"	18	18	10	21 3/8	21 3/8	19	19	9 7/8	5	9	5	Fire Department Valve with	
\vdash		1-1/4" SQUARE EDGE	18	18	10	21 3/8	21 3/8	19	19	8 7/8	5	9	5	Cap and Chain	
		2-1/2" ROLLED EDGE	18	18	10	21 3/8	21 3/8	19	19	7 5/8	5	9	5		
		SURFACE MOUNTED	21 3/16	21 3/16	10 1/2	21 3/8	21 3/8	_					quest		
		FLAT TRIM 3/8"	26	26	8	29 3/8	29 3/8	27	27	7 7/8	4	13	2 1/2		
-		1-1/4" SQUARE EDGE	26	26	8	29 3/8	29 3/8	27	27	6 7/8	4	13	2 1/2	DUAL SIDE BY SIDE	
		2-1/2" ROLLED EDGE	26	26	8	29 3/8	29 3/8	27	27	5 5/8	4	13	2 1/2	FD VALVES & EXTINGUISHER	
		SURFACE MOUNTED	29 3/16	29 3/16	8 1/2	29 3/8	29 3/8	- 07	- 07	0.7/0			quest	OR 2 FD VALVES:	
\vdash		FLAT TRIM 3/8"	26	26	10	29 3/8	29 3/8	27	27	9 7/8	5	13	5	1-1/2" or 2-1/2" with Cap and Chain Plus	
\vdash		1-1/4" SQUARE EDGE	26	26	10	29 3/8	29 3/8	27	27	8 7/8	5	13	5	Extinguisher - Cosmic & Galaxy 2-1/2 to 0	
		2-1/2" ROLLED EDGE	26	26	10 1/2	29 3/8	29 3/8	27	27	7 5/8	5	13	5		
—		SURFACE MOUNTED	29 3/16	29 3/16	10 1/2	29 3/8	29 3/8	- 17	- 44	0 7/0			quest		
\vdash		FLAT TRIM 3/8"	16	40	9	19 3/8	43 3/8	17	41	8 7/8	4 1/4	6	4 1/4	DUAL EXTINGUISHER & FD VALVE	
		1-1/4" SQUARE EDGE	16	40	9	19 3/8	43 3/8	17	41	7 7/8	4 1/4	6	4 1/4	CABINET WITH SHELF: Shelf is 12" from	
\vdash		2-1/2" ROLLED EDGE	16	40	9	19 3/8	43 3/8	17	41	6 5/8	4 1/4	6	4 1/4	bottom. Cosmic or Galaxy Extinguisher	
80	39	SURFACE MOUNTED	19 3/16	43 3/16	9 1/2	19 3/8	43 3/8	_	_	-	Upo	n Ke	quest		