

## FIRE EXTINGUISHERS - PURPLE K-C FIRE EXTINGUISHERS - Portable Handheld

Purple K extinguisher is suitable for flammable liquid hazards in public areas such as offices, classrooms, churches, garages, service bays, boats, vehicles, fuel storage and transfer areas. It is not recommended for use on sensitive electronic equipment.



**CLASS B FIRES**  
Flammable  
Liquids  
and Gases



**CLASS C FIRES**  
Energized  
Electrical  
Equipment

### SPECIFICATIONS:

PURPLE K is a high performance extinguishing agent most effective for dealing with flammable liquid fires. Suitable for use in Class B and Class C fires.

**Conforms to Test Standards:** CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711


**Operation:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation. Temperature range -65°F (-52°C) to 120°F (49°C)

**Construction:** Heavy-duty steel cylinder with rugged metal valve and siphon tube with replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact-resistant powder coat finish.

### NOTE:

This is NOT a Class K type extinguisher for use on cooking oils and grease. See our Saturn Class K wet chemical extinguisher.

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 	Optional Mounting Bracket	USCG Approved
	FPK2.5C*	Purple K	2-½ lbs.	5-½ lbs.	3-¾"	14-¾"	4-⅞"	.14 cu.ft.	10B:C	MB817C	YES
	FPK05C		5 lbs.	10 lbs.	4-¼"	16-¾"	7-¼"	.29 cu.ft.	20B:C	MB818C	YES
	FPK10C		10 lbs.	18-¼ lbs.	5-⅞"	21"	7-¾"	.5 cu.ft.	80B:C	MB846C	YES
	FPK20C		20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	.81 cu.ft.	120B:C	MB811C	YES
	FPK10CBV	Purple K Brass Valve	10 lbs.	18-¼ lbs.	5-⅞"	21"	7-¾"	.48 cu. ft.	80B:C	MB846C	YES
	FPK20CBV		20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	.81 cu.ft.	120B:C	MB811C	YES
	FPK30CBV		30 lbs.	52-¼ lbs.	7-½"	27-¾"	8-¾"	1 cu.ft.	160B:C	MB811C	YES

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - Mounting bracket available for those models at extra charge.

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



Distributor:

Project:

Contractor:

Approved By:

Date:

Architect:

Scale: N/A

Pages: 1 of 1

Item #: