

SHOWER SEAT

- Folding Shower Seat
- Teakwood Slats

Bradex™



CONSTRUCTION:

- **FRAME** fabricated of 1" dia. type 304 (18-8), 18 gauge stainless steel tubing. Heliarc welded.
- **WALL BRACKET** fabricated of 16 gauge stainless steel with stainless steel piano hinges.
- **RETAINING BRACKET** fabricated of 16 gauge stainless steel. Positive bullet-type catch holds seat securely in up or down position.
- **SEAT** consists of three handrubbed teakwood slats, each 1/2" thick and 4" wide with rounded edges.

OPERATION:

Hinged seat folds up and out of the way when not in use.

INSTALLATION:

Provide concealed backing or anchors as specified by architect before finished wall is applied. Secure to wall with mounting screws (included) at holes provided. Locate mounting holes 16-1/16" above finished floor for comfortable adult use.

GUIDE SPECIFICATION:

Folding teakwood shower seat shall be fabricated of 1/2" thick handrubbed teakwood slats secured to a stainless steel frame of 1" diameter, 18 gauge tubing. Wall bracket of 16 gauge stainless steel with heavy duty hinges.

Overall dimensions: 17"W x 16"H x 1-1/2" thick.

Folding Teakwood Shower Seat shall be Bradley Model 9559.

