



Formerly "CESCO Access Products" for 30+ Years

**C-UT – ALL PURPOSE UNINSULATED FIRE RATED ACCESS PANEL  
(FOR WALLS ONLY)**

**C-UT Standard Features:**

---

- Door: 14 gauge (1.90 mm thick) cold rolled steel
- Frame: 16 gauge (1.52 mm thick) cold rolled steel with 1" flange
- Hinge: Flush continuous piano hinge
- Latch: Knurled knob/key operated latch bolt  
Optional: mortise cylinder preparation (cylinder provided by Cierra or others)
- Finish: Phosphate dipped with factory applied prime coat  
Optional: galvanized bonderized steel or stainless steel with #4 satin polish finish
- Insulation: None

**C-UT Specifications:**

---

Model *C-UT* uninsulated fire rated access panel for all-purpose applications (walls only). Access panel shall be model *C-UT*, size \_\_\_\_\_ as manufactured by **Cierra Products** of Minneapolis, MN.

Frame shall be 16 gauge cold rolled steel with 1" flange. Door shall be fabricated from 14 gauge formed cold rolled steel. Door shall be self-latching with automatic closer and interior latch release mechanism. Hinge shall be a flush continuous piano type. Latch(es) shall be a knurled knob/key operated latch bolt (optional: preparation to receive 1-1/8" mortise cylinder – cylinder provided by Cierra or others). This assembly shall carry a 1-1/2 hour U.L. "B" label for walls only. Finish shall be phosphate dipped with factory applied prime coat (optional: galvanized bonderized steel or stainless steel with #4 satin polish finish).

Installation shall be in accordance with manufacturer's instructions. Manufacturer shall guarantee against defects in material and workmanship for a period of one year.

**C-UT Standard Sizes:**

---

<i>Std sizes (in)</i>	<i>Std Sizes (mm)</i>	<i>Weight/Latches</i>	<i>Std Sizes (in)</i>	<i>Std Sizes (mm)</i>	<i>Weight/Latches</i>
<b>08x08</b>	203x203	5/1	<b>22x30</b>	559x762	23/1
<b>10x10</b>	254x254	7/1	<b>22x36</b>	559x914	29/2
<b>12x12</b>	305x305	9/1	<b>24x24</b>	610x610	21/1
<b>12x18</b>	305x457	13/1	<b>24x30</b>	610x762	23/1
<b>12x24</b>	305x610	14/1	<b>24x36</b>	610x914	29/2
<b>14x14</b>	356x356	13/1	<b>24x48</b>	610x1219	42/2
<b>16x16</b>	406x406	12/1	<b>30x30</b>	762x762	29/1
<b>18x18</b>	457x457	14/1	<b>32x32</b>	813x813	35/1
<b>18x24</b>	457x610	19/1	<b>36x36</b>	914x914	40/2
<b>20x30</b>	508x762	21/1	<b>36x48</b>	914x1219	50/2
<b>22x22</b>	559x559	20/1			

*All units are hinged on the second dimension (height). Rough opening is door size plus 1/4".  
These panels are designed for use in wall applications only.*