



Formerly "CESCO Access Products" for 30+ Years

C-UW – UNINSULATED FIRE RATED ACCESS PANEL WITH DRYWALL CORNER BEAD (FOR WALLS ONLY)

C-UW Standard Features:

- Door: 14 gauge (1.90 mm thick) cold rolled steel
- Frame: 16 gauge (1.52 mm thick) cold rolled steel with 22 gauge galvanized drywall bead
- Hinge: Flush continuous piano hinge
- Latch: Knurled knob/key operated latch bolt
Optional: mortise cylinder preparation (cylinder provided by others)
- Finish: Phosphate dipped with factory applied prime coat
Optional: galvanized bonderized steel or stainless steel with #4 satin polish finish
- Insulation: None

C-UW Specifications:

Model C-UW uninsulated fire rated access panel for drywall applications (walls only). Access panel shall be model C-UW, size _____ as manufactured by **Cierra Products** of Minneapolis, MN.

Frame shall be 16 gauge cold rolled steel with 22 gauge galvanized drywall bead. Door shall be fabricated from 14 gauge formed cold rolled steel. Door shall be self-latching with automatic closer and interior latch release mechanism. Hinge shall be a continuous piano hinge. Latch(es) shall be a knurled knob/key operated latch bolt (optional: preparation to receive 1-1/8" mortise cylinder – cylinder provided by Cierra or others). This assembly shall carry a 1-1/2 hour U.L. "B" label for walls only. Finish shall be phosphate dipped with factory applied prime coat (optional: galvanized bonderized steel or stainless steel with #4 satin polish finish).

Installation shall be in accordance with manufacturer's instructions. Manufacturer shall guarantee against defects in material and workmanship for a period of one year.

C-UW Standard Sizes:

Std sizes (in)	Std Sizes (mm)	Weight/Latches	Std Sizes (in)	Std Sizes (mm)	Weight/Latches
08x08	203x203	5/1	22x30	559x762	23/1
10x10	254x254	7/1	22x36	559x914	29/2
12x12	305x305	9/1	24x24	610x610	21/1
12x18	305x457	13/1	24x30	610x762	23/1
12x24	305x610	14/1	24x36	610x914	29/2
14x14	356x356	13/1	24x48	610x1219	42/2
16x16	406x406	12/1	30x30	762x762	29/1
18x18	457x457	14/1	32x32	813x813	35/1
18x24	457x610	19/1	36x36	914x914	40/2
20x30	508x762	21/1	36x48	914x1219	50/2
22x22	559x559	20/1			

All units are hinged on the second dimension (height). Rough opening is door size plus 1/4".

*These panels are designed for use in wall applications only.