

RHA | Roof Hatches



Single Door



Double Door

The RHA roof hatch was developed to fill the need for a scientifically designed, mechanically efficient closure, which would provide immediate access to both flat and sloping roofs. Easily and economically installed, these roof hatches cannot be tampered with from outside the units because all fasteners are concealed, providing the highest level of security.

The RHA roof hatch is manufactured from aluminum to ensure years of dependable use, even in most extreme weather conditions. The lids are mounted on a 12" curb with cap flashing to ensure against leakage. These roof hatches come standard with compression springs, zinc plated steel hardware, and insulation in the cover and at the curb perimeter.

Product Characteristics

RHA SERIES

Cover & Liner: 11-gauge (0.090") aluminum cover with an 18-gauge aluminum liner

Curb: 11-gauge (0.090") aluminum, Optional: 11-gauge double wall curb (curb liner at exterior)

Hinge: Tamper-proof hinge contained within hatch as part of a spring assembly

Latch: Turn handle

Spring: Greased compression springs enclosed in telescopic tubes, which counterbalance the door to require no more than 10 pounds of opening force

Hardware: Zinc coated steel, Optional: Stainless steel

Insulation: 1" thick rigid fiberglass in cover and 1" at curb perimeter

Mounting Flange: 3½" on a single wall curb, 2½" on double wall curb.

Finish: Mill