

RHG | Roof Hatches



Single Door

The Babcock-Davis roof hatch was developed to fill the need for a scientifically designed, mechanically efficient closure, which would provide immediate access to both flat and sloping roofs. Easily and economically installed, Babcock-Davis roof hatches cannot be tampered with from outside the units because all fasteners are concealed, providing the highest level of security.

The Babcock-Davis B-RHG roof hatch is manufactured from galvanized steel to ensure years of dependable use, even in most extreme weather conditions. The lids are mounted on a 12" curb with cap flashing to ensure against leakage. B-D roof hatches come standard with compression springs, zinc plated steel hardware, and insulation in the cover and at the curb perimeter.



Double Door
(Shown in aluminum)

Product Characteristics

B-RHG SERIES

Cover & Liner: 14-gauge galvanized steel cover with a 22-gauge steel liner

Curb: 14-gauge galvanized steel, Optional: Double wall curb (curb liner at exterior)

Hinge: Tamper-proof hinge contained within hatch as part of a spring assembly

Latch: Turn handle

Spring: Greased compression springs enclosed in telescopic tubes, which counterbalance the door to require no more than 10 pounds of opening force

Hardware: Zinc coated steel, Optional: Stainless steel

Insulation: 1" thick rigid fiberglass in cover and 1" at curb perimeter

Mounting Flange: 3½"

Finish: Factory applied powder finish